

BOX TRAILER SPECIFICATIONS

5X3 5X4 6X4 7X4 Single Axle

Body	1.6 or 2.0 mm hot rolled black steel sheeting 305-460mm high side
Chassis	40x40x3.0 angle iron
Drawbar	65x65x6.0 angle iron
Springs	5 leaf slipper springs
Axle	39mm round dura flex to suit LM Holden bearings
Wheels	13" or 14" or 15" optional black rims and new recap tyres
Coupling	50mm plunger type
Floor	1.6mm flat sheet or 2.1mm chequered plate steel
Load rating	Unbraked 750kg Braked 1180-1450kg
Paint	Zinc enriched primer, top coated with quality enamel finish

7'x4'6" 7'x5' 8X5 Single Axle

Body	2.0 mm hot rolled black steel sheeting 305-460mm high side
Chassis	40x40x3.RHS
Drawbar	75x50x3.RHS
Springs	5 leaf slipper springs
Axle	39mm round dura flex to suit LM Holden bearings
Wheels	13" or 14" or 15" optional black rims and new recap tyres
Coupling	50mm plunger type
Floor	2.1mm flat sheet or 2.1mm chequered plate steel
Load rating	Unbraked 750kg Braked 1180-1450kg
Paint	Zinc enriched primer, top coated with quality enamel finish

8X5 9X5 10X6 12X6 Up to 1990kg capacity Tandem Trailers

Body	2.1 mm chequered plate side and floor rolled all in one body 305-460 high side
Floor	2.1mm chequered plat rolled with sides
Chassis	8x5 & 9x5 = 50x50x3.0 RHS 10x6 & 12x6 = 75x50x3.0 RHS
Drawbar	100x50x3.0 RHS
Springs	6 leaf tandem springs Optional 6 leaf tandem load sharing rocker springs
Axle	8x5 & 9x5 = 40mm square 10x6 & 12x6 = 45mmsquare
Bearings	40mm axles = composite bearings 45mm axles = Ford bearings
Brakes	9x1 ¾ hydraulic override on front axle Optional – 10"x2" electric inc hand brake on front axle
Wheels	13" or 14" or 15" new black rims inc new light truck tyres
Coupling	2000kg hydraulic override plunger tyre 50mm Optional – 3500kg fixed inc hand brake for electric brakes
Paint	Zinc enriched primer, top coated with quality enamel finish
Tailgate	Opening front and rear
Taillights	3 in 1 with bulbs 12 or 24 volt Optional – LED lights 12 to 24 voltage